D	U	RA	E	1	®
Rech	narg	eable			

BEI

**FEA** 

## CEF23P

## Charge Sizes: AA , AAA

## Charger for NiMH Batteries

	Technical Specifications						
DURACELL	Battery Charger:	Class 2, Integrated Power Supply					
	Plug:	Direct, Interchangeable Plug Matches Local Requirements					
	Battery Type/Fit:	NiMH: 1 or 4 AA/HR6, NiMH: 1 or 4 AAA/HR03					
	Typical Weight:	171g					
	Input:	100-240V AC, 50-60 Hz					
	Output:	AA/HR6: 1.5V DC 600 mA, AAA/HR03 1.5V DC 600 mA					
	Operating Temp:	0°C - 35°C (32°F - 95°F)					
	Dimensions:	130 mm (L) x 80 mm (W) x 30 mm (H)					
<b>NEFITS</b> Convenient & Portable to Charge On- The-Go High Tech Devices 4 AA Ready in 3 hours*							
		through unplugged charger with fully charged batteries					

- •Four Independent Channel Charging
- •Charges AA and AAA simultaneously
- Interchangeable plugs and car adaptor
- •International Charge Capability- device can be used worldwide with suitable converter plug

SAFETYMicroprocessor Controlled• Charge Termination based on -dV/dt, temperature, and/or built in timer• Primary battery protection- will not charge non-rechargeable batteries• Over-temperature shut off- prevents overheat of battery• Over-charge protection- prevents battery damage• Low- voltage battery protection- prevents overheat and damage to battery• Power Protection Circuit- resets whenever battery is removed or power is interrupted• Enclosed charging compartment provides protection



Berkshire Corporate Park Bethel, CT 06801 U.S.A. Tel: Toll free 1.800.544.5454 Web: www.Duracell.com

\*Approx. 90% of full charge, when using Duracell AA1300 mAh NiMH Batteries.

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.